



PREMIUM FLUSH MOUNTED VENT & GRILL COVERS

Removable Access Panel [AP 12]

Magnetic Access Cover - Accessible Opening 10" x 10" (254mm x 254mm)
14 1/4" x 14 1/4" x 1/2" (362mm x 362mm x 12mm) over all dimensions.

Application:

- Designed for 1/2" & 5/8" thick drywall installations.
- Ceiling and wall installations.
- Water shut off valves, plumbing clean out.

Features:

- Magnetic Removable Access Door
- Flush smooth Clean Finish
- Triple Fibre Reinforced Cement Board.
- 24 gauge galvanized satin coat steel frame complete with beaded edge.
- 4 Rare Earth Magnets - .250" Diameter x .060" Thick
- Easy Installation, primed and ready for paint.
- Fire Rated, Non-Flammable.
- Impact Resistant.
- Moisture and Water Resistant, Mold Resistant.
- Eco- Friendly Manufacturing and Non-Hazardous.

Product Specifications:

- Over 100 square inches (645 square cm) of accessible area.
- Overall dimensions 14 1/4" x 14 1/4" x 1/2" (369mm x 369mm x 12mm)

Material Specifications:

- Raw Material - Magnesium sulphate cement, plant fibre, glass fibre cloth, perlite
- Density - 0.95 g/cm³
- Water Content - 12%
- Chloride Ion Content - 0%
- Formaldehyde Release - 0%
- Asbestos Content - 0%
- Fire resistance - Incombustibility A1 Class (GB 8624-2006/EN 13501-1)
- Water Absorption - 27%
- Resistant Bending Strength - 8 MPa
- Impact Resistance - 1.5 J/m
- Nail-Withdrawal strength - 16 N/mm
- Water Permeability - No water vapour after 24 hours' test
- Refractoriness (Pyrometric cone Test) - 4H
- pH Value - 6.7{8.0
- Thermal conductivity - 0.2 W/(mK)
- Moisture Movement - 0.25 %
- Heat Shrinkage Rate - 0.05
- Freeze Thaw - No distortion after 25 repeated cycles of freezing and thawing.

